

DE 4328619

DELPHION

No active tr.

select CR

St

RESEARCH

PRODUCTS

INSIDE DELPHION

Log Out Work Files Saved Searches

My Account

Search: Quick/Number Boolean Advanced Der


Derwent Record

Em

View: [Expand Details](#) Go to: [Delphion Integrated View](#)

Tools: Add to Work File: Create new Wor

Derwent Title: **Prod. of and partially reinforced cast aluminium alloy component - comprises a reinforcing element formed of a spray-compacted aluminium alloy and inserted into the casting mould for the component**

Original Title:  **EP0640759A1: Partially reinforced aluminium cast construction part and method of manufacturing same**

Assignee: **PEAK WERKSTOFF GMBH Non-standard company**


Inventor: **HUMMERT K; SCHATTEVOY R;**

Accession/Update: **1995-092386 / 199722**

IPC Code: **B22D 19/02 ; F02F 3/00 ; B22D 15/02 ; B22D 19/00 ; B22D 19/14 ; C23C 4/12 ; F02F 3/12 ;**

Derwent Classes: **M22; P53; Q52;**

Manual Codes: **M22-G03K(Making specific cast products)**



Derwent Abstract: (EP0640759A) The component (1) consists of an aluminium alloy casting (2) and a reinforcing element (3) which is at least partially surrounded by the basic material of the casting (2). The reinforcing element (3) consists of a spray-compacted aluminium alloy which (within the joint regions) forms an integral, firm material bond with the casting (2).


The method for producing the component (1) includes: (a) forming of a spray-compacted reinforcing element (3) which defines at least a part of the finished component (1); (b) insertion of the element (3) into a casting mould for the component; and (c) filling the remaining mould space with aluminium alloy melt.

Use - In motor manufacturing industries.

Advantage - Partially reinforced cast aluminium alloy castings, with an integral bond between the cast and reinforcing materials, are produceable in a cost-effectively manner. **CLAIMED METHOD** - The reinforcing element (3) is produced as an extruded section. Alternatively, it is produced as a forging. Such an element is preheated in the mould. The mould is filled with aluminium alloy melt at a velocity which is sufficient for washing away the oxide layers that have formed on the surface of the reinforcing element. The washing-away process is controlled by the choice of the pouring locations and/or by stirring and/or by creation of eddy currents by means of induction coils.

Images:

BEST AVAILABLE COPY



Dwg.1/5, Dwg.4a/5, Dwg.4a/5

Family: PDF Patent Pub. Date Derwent Update Pages Language IPC Code

☒ EP0640759A1 * 1995-03-01 199513 11 German F02F 3/00

Des. States: (R) AT ES FR GB IT NL SE

Local appls.: EP1994000112615 Filed:1994-08-12 (94EP-0112615)

☒ ES2098085T3 = 1997-04-16 199722 Spanish F02F 3/00

Local appls.: Based on EP00640759 (EP 640759)

EP1994000112615 Filed:1994-08-12 (94EP-0112615)

☒ EP0640759B1 = 1997-03-05 199714 11 German F02F 3/00

Des. States: (R) AT ES FR GB IT NL SE

Local appls.: EP1994000112615 Filed:1994-08-12 (94EP-0112615)

☒ DE4328619C2 = 1995-08-10 199536 9 German B22D 19/02

Local appls.: DE1993004328619 Filed:1993-08-26 (93DE-4328619)

☒ DE4328619A1 = 1995-03-02 199514 9 German B22D 19/02

Local appls.: DE1993004328619 Filed:1993-08-26 (93DE-4328619)

INPADOC Show legal status actions

Legal Status:

First Claim: 1. Bauteil (1) bestehend aus einem Al-Gußteil (2) und einem von dessen Grundwerkst.
Show all claims zumindest partiell durch Eingießen umschlossenen Verstärkungsteil (3), das aus einem
sprühkompaktierten Al-Werkstoff besteht und in den Fügezonen mit dem Al-Gußteil (2) e
vollständigen festen Materialverbund eingeht.

Priority Number:

Application Number	Filed	Original Title
DE1993004328619	1993-08-26	Partiell verstärktes Al-Gußbauteil und Verfahren zu dessen Herstellung

Citations:

PDF	Patent	Original Title
	DE3518058	KOLBEN FUER VERBRENNUNGSMOTOREN

BEST AVAILABLE COPY

<input checked="" type="checkbox"/>		
<input checked="" type="checkbox"/>	<u>DE4010474</u>	LEICHTMETALLKOLBEN
<input checked="" type="checkbox"/>	<u>EP0262869</u>	PARTICULATE AL ALLOY COMPOSITES
<input checked="" type="checkbox"/>	<u>JP56166368</u>	SLIDING MEMBER
<input checked="" type="checkbox"/>	<u>JP59231163</u>	NAINENKIKANNOSHIRINDAHETSUDO
		Msg: 02Jnl.Ref
		Msg: 2.Jnl.Ref

⌘ Title Terms: PRODUCE REINFORCED CAST ALUMINIUM ALLOY COMPONENT COMPRISE
REINFORCED ELEMENT FORMING SPRAY COMPACT ALUMINIUM ALLOY
INSERT CAST MOULD COMPONENT

[Pricing](#) [Current charges](#)

Derwent Searches: [Boolean](#) | [Accession/Number](#) | [Advanced](#)

Data copyright Thomson Derwent 2003



Copyright © 1997-2006 The Tho

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact U](#)